

ProAct™

CONDUCTIVE POLYMER FLEXIBLE ANODE

PRODUCT DESCRIPTION

The conductive polymer flexible anode is a cable-shaped impressed-current anode consisting of a conductive, stable modified polymer anode body and a copper cable core conductor. It offers good flexibility, strong resistance to mechanical damage, and excellent chemical stability.

The conductive polymer flexible anode is suitable for a wide range of soil environments and is particularly well suited for high-resistivity or variable-resistivity conditions.

The anode consists of a conductive polymer layer, copper wire, coke breeze layer, acid- and alkali-resistant wrapped fabric, and abrasion-resistant braid.

PRODUCT PERFORMANCE

Environmental Adaptability

- The flexible anode structure allows adaptation to complex installation conditions and irregular anode layouts.

Current Output Stability

- Stable current output supports reliable cathodic protection performance during long-term operation.

Service Life

- Long service life under designed operating conditions helps reduce maintenance and replacement requirements.




PRODUCT FEATURES

Backfill Filling Technology

- Petroleum coke backfill is filled using patented filling equipment combined with mobile vibration technology to ensure dense and uniform backfill.

Installation & Reliability

- Flexible length design simplifies installation. The anode can be cut to the required length on site, enabling fast and safe construction.



Reference	Title
ASTM B193-02	STANDARD TEST METHOD FOR RESISTIVITY OF ELECTRICAL CONDUCTOR MATERIALS
NACE RP0285	STANDARD RECOMMENDED PRACTICE CORROSION CONTROL OF UNDERGROUND STORAGE TANK SYSTEMS BY CATHODIC PROTECTION
EN 12954-2001	CATHODIC PROTECTION OF BURIED OR IMMERSED METALLIC STRUCTURES - GENERAL PRINCIPLES AND APPLICATION FOR PIPELINES
EN 13636-2004	CATHODIC PROTECTION OF BURIED METALLIC TANKS AND RELATED PIPING

PRODUCT PARAMETERS

Description	Technical Data
Maximum Output Current	52 mA/m
Minimum Installation and Storage Temperature	-18°C
Minimum Bending Radius	500mm
Lifespan	≥25 years
Applications	Tanks; Oil and Gas Facilities

MODELS AND SPECIFICATIONS

Model	Cable Size	Conductive polymer diameter	Nominal diameter	Weight
AT-AF-01	6 AWG	13mm	38mm	1.4~1.6Kg/m



For further information, please contact Advance Technology.



Canada

290 North Queen St
Suite 208,
Etobicoke, Ontario
Canada, M9C 5L2

Phone: + 1 416 433 3186

advance-technology.com
consult@advance-tech.ca